
Geofront Documentation

Release 0.4.0

Hong Minhee

Aug 06, 2017

Contents

1 Situations	3
2 Idea	5
3 Prerequisites	7
4 Author and license	9
5 Missing features	11
6 User's guide	13
6.1 Installation	13
6.2 How to contribute	16
6.3 Geofront Changelog	16
7 References	21
7.1 HTTP API	21
7.2 CLI	27
7.3 Configuration	28
7.4 geofront — Simple SSH key management service	33
8 Indices and tables	61
HTTP Routing Table	63
Python Module Index	65

Geofront is a simple SSH key management server. It helps to maintain servers to SSH, and `authorized_keys` list for them. [Read the docs](#) for more details.

CHAPTER 1

Situations

- If the team maintains `authorized_keys` list of all servers owned by the team:
 - When someone joins or leaves the team, all lists have to be updated.
 - *Who* do update the list?
- If the team maintains shared private keys to SSH servers:
 - These keys have to be expired when someone leaves the team.
 - There should be a shared storage for the keys. (Dropbox? *srsly*?)
 - Everyone might need to add `-i` option to use team's own key.
- The above ways are both hard to scale servers. Imagine your team has more than 10 servers.

CHAPTER 2

Idea

1. Geofront has its own *master key*. The private key is never shared. The master key is periodically and automatically regened.
2. Every server has a simple `authorized_keys` list, which authorizes only the master key.
3. Every member registers their own public key to Geofront. The registration can be omitted if the key storage is GitHub, Bitbucket, etc.
4. A member requests to SSH a server, then Geofront *temporarily* (about 30 seconds, or a minute) adds their public key to `authorized_keys` of the requested server.

CHAPTER 3

Prerequisites

- Linux, BSD, Mac
- Python 3.3+
- Third-party packages (automatically installed together)
 - [Paramiko](#) 2.0.1+ (which requires [cryptography](#))
 - [Werkzeug](#) 0.11+
 - [Flask](#) 0.10.1+
 - [OAuthLib](#) 1.1.1+
 - [Apache Libcloud](#) 1.1.0+
 - [Waitress](#) 1.0.2+
 - [singledispatch](#) (only if Python is older than 3.4)
 - [typing](#) (only if Python is older than 3.5)
 - [typeguard](#) 2.1.1+

CHAPTER 4

Author and license

Geofront is written by [Hong Minhee](#), maintained by [Spoqa](#), and licensed under [AGPL3](#) or later. You can find the source code from [GitHub](#):

```
$ git clone git://github.com/spoqa/geofront.git
```


CHAPTER 5

Missing features

- Google Apps backend [[#3](#)]
- Fabric integration
- PuTTY integration

(Contributions would be appreciated!)

CHAPTER 6

User's guide

Installation

You can easily install Geofront server using pip:

```
$ pip3 install Geofront
```

Running server

Geofront server requires a configuration file. Configuration file is a typical Python script. The server is sensitive to the values of some uppercase variables like `TEAM`, `KEY_STORE`, and `MASTER_KEY_BITS`. The filename of the configuration is not important, but recommend to use `.cfg.py` suffix. You also can find an example configuration in the Geofront repository: `example.cfg.py`.

See also:

Configuration The reference manual for Geofront server configuration.

If a configuration file is ready you can run the server right now. Suppose the configuration file is `geofront.cfg.py`.

geofront-server command provides several options like `--host`, and requires a configuration filename as its argument.

```
$ geofront-server -p 8080 geofront.cfg.py
```

It might be terminated with the following error message:

```
$ geofront-server -p 8080 geofront.cfg.py
usage: geofront-server [...] FILE
geofront-server: error: no master key;
try --create-master-key option if you want to create one
```

It means `MASTER_KEY_STORE` you configured has no master key yet. `--create-master-key` option creates a new master key if there's no master key yet, and then stores it into the configured `MASTER_KEY_STORE`.

```
$ geofront-server -p 8080 --create-master-key geofront.cfg.py
no master key;  create one...
created new master key: 2b:d5:64:fd:27:f9:7a:6a:12:7d:88:76:a7:54:bd:6a
serving on http://0.0.0.0:8080
```

If it successfully starts serving it will show you the bound host and port.

Reverse proxy

Application servers typically run behind the reverse proxy like `Nginx`. Here's an example configuration for Geofront server behind Nginx reverse proxy:

```
# Redirect all HTTP requests to HTTPS.
# We highly recommend to expose Geofront server only through HTTPS.
server {
    listen 80;
    server_name geofront-example.org;
    rewrite ^(.*)$ https://geofront-example.org$1;
}

# Forward all requests to https://geofront-example.org to internal
# http://127.0.0.1:8080.
server {
    listen 443 ssl;
    server_name geofront-example.org;
    access_log /var/log/nginx/geofront/access.log;
    error_log /var/log/nginx/geofront/error.log;

    ssl on;
    ssl_certificate /path/to/ssl_cert_chain.pem;
    ssl_certificate_key /path/to/ssl_cert.pem;

    # HSTS: https://developer.mozilla.org/en-US/docs/Web/Security/HTTP_strict_transport_
    ↪security
    add_header Strict-Transport-Security "max-age=31536000";

    location / {
        proxy_pass http://127.0.0.1:8080;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    }
}
```

Using `geofront-cli`

Every team member who want to use Geofront has to install a client for Geofront. `geofront-cli` is the reference implementation of Geofront client. It can be installed using `pip`:

```
$ pip install geofront-cli
```

To setup what Geofront server to use use `geofront-cli start` command. It will show a prompt:

```
$ geofront-cli start
Geofront server URL:
```

Type the server URL, and then it will open an authentication page in your default web browser:

```
$ geofront-cli start
Geofront server URL: https://geofront-example.org/
Continue to authenticate in your web browser...
Press return to continue
```

That's done. Setup process is only required at first. You can show the list of available remotes using **geofront-cli remotes**:

```
$ geofront-cli remotes
web-1
web-2
...
```

For more details on **geofront-cli**, read the manual of its `README.rst`, or use `geofront-cli --help` option.

Remote colonization

Until a remote server authorizes the master key you can't access to the remote using **geofront-cli**. So the master key needs to be added to remote's `authorized_keys` list. Geofront calls it *colonization*. You can colonize a remote using **geofront-cli colonize** command. Surely the following command has to be run by who can access to it:

```
$ geofront-cli remotes
web-1
web-2
...
$ geofront-cli colonize web-1
```

You can understand **geofront-cli colonize** is `ssh-copy-id` for Geofront. Once colonized remote is accessible by every team member unless you configured more fine-grained ACL. (See also [PERMISSION_POLICY](#) if you're interested in ACL.)

SSH through Geofront

If a remote is once colonized any team member can **ssh** to it through Geofront. Use **geofront-cli ssh** command:

```
$ geofront-cli ssh web-1
Last login: Sat May 3 16:32:15 2014 from hong-minhees-macbook-pro.local
$
```

How to contribute

License agreement

All contributed codes have to be free software licensed under the terms of the [GNU Affero General Public License Version 3](#) or any later version. We treat all pull requests imply agreement of it, but if a significant amount of code is involved, it is safest to mention in the pull request comments that you agree to let the patch be used under the GNU Affero General Public License Version 3 or any later version as part of the Geofront code.

Coding style

- Follow [PEP 8](#) except you can limit all lines to a maximum of 80 characters (not 79).
- Order `imports` in lexicographical order.
- Prefer relative `imports`.
- All functions, classes, methods, attributes, and modules should have the docstring.

Tests

- All code patches should contain one or more unit tests of the feature to add or regression tests of the bug to fix.
- You can run the test suite using `runtests.sh` script. It installs libraries for testing as well if not installed.
- Or you can simply run `py.test` command if you have all dependencies for testing.
- Some tests would be skipped unless you give additional options. You can see the list of available options in *custom options* section of `py.test --help`.
- All commits will be tested by [Travis CI](#).

Geofront Changelog

Version 0.4.0

Released on March 30, 2017.

- Geofront now supports ECDSA key. Under the hood, `geofront.keystore.parse_openssh_pubkey()` function becomes to be possible to parse ECDSA public keys. [[#14](#)]
- Geofront now supports Atlassian Bitbucket Cloud. See also `geofront.backends.bitbucket` module. [[#4](#)]
- Geofront now can generate other than RSA master key (e.g. ECDSA). The new configuration `MASTER_KEY_TYPE` is added to choose the type of the master key Geofront will generate. It's `RSAKey` by default.
- Added `geofront.backends.oauth` module which provides base team implementations for OAuth.
- Added `key_type` optional parameter to `renew_master_key()` function, `PeriodicalRenewal` class constructor, and `regenerate()` function.
- Since `key_type` now can be other than `RSAKey`, the `bits` optional parameter of `renew_master_key()` function, `PeriodicalRenewal` class constructor, and `regenerate()` function now have the default value `None` instead of `2048`. `None` automatically choose the appropriate bits of the `key_type`.

- Added `generate_key()` function and `KeyGenerationError` that it raises.
- Added `alias_namer` option to `CloudRemoteSet` constructor.
- Added `geofront.team.GroupSet` type which is alias of `AbstractSet[Hashable]`.
- Now master key can be found without token through `GET /masterkey/` API. The server root `GET /` also became to contain a `Link` header to it and "master_key_url" field.
- Deprecated `GET /tokens/(token_id:token_id)/masterkey/`. Use `GET /masterkey/` instead. The existing url redirects to the new url `GET /masterkey/` with 301 Moved Permanently.
- Fixed bug that `CloudKeyStore.list_keys()` sometimes returned an empty set even if there were stored keys.
- Geofront becomes to require Paramiko 2.0.1 or higher.
- Geofront becomes to require Werkzeug 0.11 or higher.
- Geofront becomes to require Flask 0.10.1 or higher.
- Geofront becomes to require Apache Libcloud 1.1.0 or higher.
- Geofront becomes to require OAuthLib 1.1.1 or higher.
- Geofront becomes to require Waitress 1.0.2 or higher.
- Geofront becomes to require typeguard 2.1.1 or higher.
- `geofront.util` is gone now. Geofront instead became to require `typing` and `typeguard`.

Version 0.3.2

Released on March 7, 2016.

- Added `RemoteSetUnion` to make union view of multiple remote sets.
- Fixed `AttributeError` on `StashKeyStore.register()` or `StashKeyStore.deregister()` being called.

Version 0.3.1

Released on January 19, 2016.

- Added `RemoteSetFilter` to dynamically filter set of remotes.
- Fixed a regression bug introduced since 0.3.0 (`9db44659c423ed33a89de712fb645186b7c722cc`) that `GitHubOrganization` fails to authenticate. [[#12](#)]

Version 0.3.0

Released on January 15, 2016.

- Geofront becomes to require Paramiko 1.15.0 or higher.
- Added save check for `AuthorizedKeyList`. [[#5](#)]
- `Team.request_authentication()` method becomes to no more take `auth_nonce` and return `AuthenticationContinuation` value instead of simple url `str`, so that arbitrary value more general than simple nonce `str` can be shared between `request_authentication()` and `Team.authenticate()`. If arbitrary nonce is needed, `request_authentication()` method has to generate one by itself.

- Geofront now supports Atlassian Bitbucket Server (which was Stash). See also `geofront.backends.stash` module.
- `TwoPhaseRenewal` became to raise `ConnectionError` with attempted remote address instead of `socket.gaierror` which is hard to troubleshoot.
- Fixed signature mismatch errors of `CloudMasterKeyStore` when it's used with AWS S3.

Version 0.2.2

Released on July 8, 2014.

- Became to depend on apache-libcloud 0.15.0 or later.
- Added HSTS support:
 - Added `ENABLE_HSTS` configuration.
 - Added `--force-https` option to `geofront-server` command.
- Fixed a bug of `KeyPairDoesNotExistError.save()` method that leaks `MalformedResponseError` raised by `EC2NodeDriver` which ought to raise proper `libcloud.compute.types.KeyPairDoesNotExistError`.

Version 0.2.1

Released on June 16, 2014.

- Fixed an authentication bug of `TwoPhaseRenewal` raised due to not specify login username.
- More detailed message logging of exceptions that rise during master key renewal.

Version 0.2.0

Released on May 3, 2014.

- Added `list_groups()` method to `Team` interface.
- Added `list_groups()` method to `GitHubOrganization` class.
- Removed an unnecessary dependency to `enum34` on Python 3.3.
- Added `geofront.backends.cloud` module.
 - `geofront.masterkey.CloudMasterKeyStore` is moved to `geofront.backends.cloud.CloudMasterKeyStore`.
 - `geofront.remote.CloudRemoteSet` is moved to `geofront.backends.cloud.CloudRemoteSet`.
- `Remote` now has `metadata` attribute.
- `CloudRemoteSet` fills `metadata` of the resulted `Remote` objects if the given driver supports.
- Now depends on `singledispatch` if Python is older than 3.4.
- Added `PermissionPolicy` interface.
- Added `DefaultPermissionPolicy` class.
- Added `GroupMetadataPermissionPolicy` class.

- Added new PERMISSION_POLICY configuration.
- Added `geofront.backends.dbapi` module.
- Added `geofront-key-regen` command.
- HTTP APIs became more RESTful. Now it has the root endpoint which provides the link to create a new token, and the token API provides several links to subresources as well.
- Added new MASTER_KEY_BITS configuration.
- Added new bits optional parameters to `renew_master_key()`, `PeriodicalRenewal`, and `regenerate()`.
- Added `CloudKeyStore`. [#2]
- Added `CloudMasterPublicKeyStore`. [#2]

Version 0.1.1

Released on April 22, 2014.

- Fixed `TypeError` that rises when `CloudMasterKeyStore` is used with AWS S3 driver.
- Added `--trusted-proxy` option to `geofront-server` command. It's useful when the server is run behind a reverse proxy.
- Added token no-op API: `GET /tokens/(token_id:token_id)/`.

Version 0.1.0

First alpha release. Released on April 21, 2014.

References

HTTP API

Server version

The release policy of Geofront follows [Semantic Versioning](#), and the HTTP API which this docs covers also does the same. You can treat what you could do on Geofront 1.2.3:

- might be broken on Geofront 2.0.0;
- shouldn't be broken 1.3.0;
- must not be broken on Geofront 1.2.4.

Also broken things on Geofront 1.2.3 might be fixed on Geofront 1.2.4.

So how does the server tell its version through HTTP API? It provides two headers that are equivalent:

Server Which is a standard compliant header. The form follows also the standard e.g. `Geofront/1.2.3`.

X-Geofront-Version Which is a non-standard extended header. The form consists of only the version number e.g. `1.2.3`.

These headers even are provided when the response is error:

```
HTTP/1.0 404 Not Found
Content-Length: 9
Content-Type: text/plain
Date: Tue, 01 Apr 2014 17:46:36 GMT
Server: Geofront/0.9.0
X-Geofront-Version: 0.9.0
```

```
Not Found
```

Endpoints

GET /masterkey/

Public part of the master key in OpenSSH authorized_keys (public key) format.

```
GET /masterkey/ HTTP/1.1  
Accept: text/plain
```

```
HTTP/1.1 200 OK  
Content-Type: text/plain  
  
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjbC.../MuLLzC/m8Q==
```

Status Codes

- 200 OK – when the master key is available
- 500 Internal Server Error – when the master key is unavailable

GET /

The endpoint of HTTP API which provide the url to create a new token.

```
GET / HTTP/1.1  
Accept: application/json
```

```
HTTP/1.0 200 OK  
Content-Type: application/json  
Link: <https://example.com/tokens/>; rel=tokens  
Link: <https://example.com/masterkey/>; rel=masterkey  
  
{  
  "master_key_url": "https://example.com/masterkey/",  
  "tokens_url": "https://example.com/tokens/"  
}
```

Response Headers

- Link – the url to create a new token. the equivalent to the response content

Status Codes

- 200 OK – when the server is available

New in version 0.4.0: Added "master_key_url" field in the result and Link header of rel=masterkey.

New in version 0.2.0.

POST /tokens/ (token_id: token_id) /remotes/

alias/ Temporarily authorize the token owner to access a remote. A made authorization keeps alive in a minute, and then will be expired.

```
POST /tokens/0123456789abcdef/remotes/web-1/ HTTP/1.1  
Accept: application/json  
Content-Length: 0
```

```
HTTP/1.1 200 OK  
Content-Type: application/json
```

```
{
  "success": "authorized",
  "remote": {"user": "ubuntu", "host": "192.168.0.5", "port": 22},
  "expires_at": "2014-04-14T14:57:49.822844+00:00"
}
```

Parameters

- **token_id** (`str`) – the token id that holds the identity
- **alias** (`str`) – the alias of the remote to access

Status Codes

- **200 OK** – when successfully granted a temporary authorization
- **404 Not Found** – (not-found) when there's no such remote

GET /tokens/ (token_id: token_id) /keys/**fingerprint: fingerprint/** Find the public key by its fingerprint if it's registered.

```
GET /tokens/0123456789abcdef/keys/50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47/
  ↪ HTTP/1.1
Accept: text/plain
```

```
HTTP/1.1 200 OK
Content-Type: text/plain

ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCom2CDLekY...5CeYsvSdrTWA5 ==
.../MuLLzC/m8Q==
```

Parameters

- **token_id** (`str`) – the token id that holds the identity
- **fingerprint** (`bytes`) – the fingerprint of a public key to find

Status Codes

- **200 OK** – when the public key is registered
- **404 Not Found** – (not-found) when there's no such public key

DELETE /tokens/ (token_id: token_id) /keys/**fingerprint: fingerprint/** Delete a public key.

```
DELETE /tokens/0123456789abcdef/keys/
  ↪50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47/ HTTP/1.1
Accept: application/json
```

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "72:00:60:24:66:e8:2d:4d:2a:2a:a2:0e:7b:7f:fc:af": 
    "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCom2CDLekY...5CeYsvSdrTWA5 ",
  "78:8a:09:c8:c1:24:5c:89:76:92:b0:1e:93:95:5d:48": 
    "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEA16iSKKjFHOgj...kD62SYXNKY9c= ",
  "ab:3a:fb:30:44:e3:5e:1e:10:a0:c9:9a:86:f4:67:59":
```

```
        "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAQEAzzF8c07pzbKk...r+b6Q9VnWWQ=="
    }
```

Parameters

- **token_id** (`str`) – the token id that holds the identity
- **fingerprint** (`bytes`) – the fingerprint of a public key to delete

Status Codes

- **200 OK** – when the public key is successfully deleted
- **404 Not Found** – (not-found) when there's no such public key

GET /tokens/ (token_id: *token_id*) /authenticate/

Finalize the authentication process. It will be shown on web browser.

Parameters

- **token_id** (`str`) – token id created by `create_access_token()`

Status Codes

- **400 Bad Request** – when authentication is failed
- **404 Not Found** – when the given `token_id` doesn't exist
- **403 Forbidden** – when the `token_id` is already finalized
- **200 OK** – when authentication is successfully done

GET /tokens/ (token_id: *token_id*) /masterkey/

Public part of the master key in OpenSSH authorized_keys (public key) format.

```
GET /tokens/0123456789abcdef/masterkey/ HTTP/1.1
Accept: text/plain
```

```
HTTP/1.1 301 Moved Permanently
Content-Type: text/plain
```

```
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjbC.../MuLLzC/m8Q==
```

Parameters

- **token_id** (`str`) – the token id that holds the identity

Status Codes

- **200 OK** – when the master key is available
- **500 Internal Server Error** – when the master key is unavailable

Deprecated since version 4.0.0: Use [GET /masterkey/](#) instead.

Changed in version 4.0.0: It now responds with **301 Moved Permanently** instead of **200 OK**. It redirects to [GET /masterkey/](#) which is the new master key url.

GET /tokens/ (token_id: *token_id*) /remotes/

List all available remotes and their aliases.

```
GET /tokens/0123456789abcdef/remotes/ HTTP/1.1
Accept: application/json
```

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "web-1": {"user": "ubuntu", "host": "192.168.0.5", "port": 22},
  "web-2": {"user": "ubuntu", "host": "192.168.0.6", "port": 22},
  "web-3": {"user": "ubuntu", "host": "192.168.0.7", "port": 22},
  "worker-1": {"user": "ubuntu", "host": "192.168.0.25", "port": 22},
  "worker-2": {"user": "ubuntu", "host": "192.168.0.26", "port": 22},
  "db-1": {"user": "ubuntu", "host": "192.168.0.50", "port": 22},
  "db-2": {"user": "ubuntu", "host": "192.168.0.51", "port": 22}
}
```

Parameters

- **token_id** (str) – the token id that holds the identity

Status Codes

- 200 OK – when listing is successful, even if there are no remotes

GET /tokens/ (token_id: token_id) /keys/

List registered keys to the token owner.

```
GET /tokens/0123456789abcdef/keys/ HTTP/1.1
Accept: application/json
```

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47":
    "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQgQDAEMUvjBcX.../MuLLzC/m8Q==",
  "72:00:60:24:66:e8:2d:4d:2a:2a:a2:0e:7b:7f:fc:af":
    "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCom2CDLekY...5CeYsvSdrTWA5",
  "78:8a:09:c8:c1:24:5c:89:76:92:b0:1e:93:95:5d:48":
    "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAIAEA16iSKKjFHOgj...kD62SYXNKY9c=",
  "ab:3a:fb:30:44:e3:5e:1e:10:a0:c9:9a:86:f4:67:59":
    "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAQEAzzF8c07pzgKk...r+b6Q9VnWWQ=="
}
```

Parameters

- **token_id** (str) – the token id that holds the identity

Status Codes

- 200 OK – when listing is successful, even if there are no keys

POST /tokens/ (token_id: token_id) /keys/

Register a public key to the token. It takes an OpenSSH public key line through the request content body.

```
POST /tokens/0123456789abcdef/keys/ HTTP/1.1
Accept: application/json
Content-Type: text/plain

ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQgQDAEMUvjBcX.../MuLLzC/m8Q==
```

```
HTTP/1.1 201 Created
Content-Type: text/plain
Location: /tokens/0123456789abcdef/keys/
←50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjBcX.../MuLLzC/m8Q==
```

Parameters

- **token_id** (str) – the token id that holds the identity

Status Codes

- 201 Created – when key registration is successful
- 400 Bad Request – (unsupported-key-type) when the key type is unsupported, or (invalid-key) the key format is invalid, or (duplicate-key) the key is already used
- 415 Unsupported Media Type – (unsupported-content-type) when the Content-Type is not *text/plain*

PUT /tokens/ (token_id: token_id) /

Create a new access token.

```
PUT /tokens/0123456789abcdef/ HTTP/1.1
Accept: application/json
Content-Length: 0
```

```
HTTP/1.1 202 Accepted
Content-Type: application/json
Date: Tue, 15 Apr 2014 03:44:43 GMT
Expires: Tue, 15 Apr 2014 04:14:43 GMT
Link: <https://example.com/login/page/?redirect_uri=...>; rel=next
{
  "next_url": "https://example.com/login/page/?redirect_uri=..."
}
```

Parameters

- **token_id** (str) – an arbitrary token id to create. it should be enough random to avoid duplication

Status Codes

- 202 Accepted – when the access token is prepared

Response Headers

- **Link** – the link owner's browser should redirect to

GET /tokens/ (token_id: token_id) /

The owner identity that the given token holds if the token is authenticated. Otherwise it responds 403 Forbidden, 404 Not Found, 410 Gone, or 412 Precondition Failed. See also `get_identity()`.

```
GET /tokens/0123456789abcdef/ HTTP/1.1
Accept: application/json
```

```
HTTP/1.0 200 OK
Content-Type: application/json
Link: <https://example.com/tokens/0123456789abcdef/remo...>; rel=remotes
Link: <https://example.com/tokens/0123456789abcdef/keys/>; rel=keys
Link: <https://example.com/masterkey/>; rel=masterkey

{
  "identifier": "dahlia",
  "team_type": "geofront.backends.github.GitHubOrganization",
  "remotes_url": "https://example.com/tokens/0123456789abcdef/remotes/",
  "keys_url": "https://example.com/tokens/0123456789abcdef/keys/",
  "master_key_url": "https://example.com/masterkey/"
}
```

Parameters

- **token_id** (`str`) – the token id that holds the identity

Response Headers

- **Link** – the url to list remotes (`rel=remotes`), public keys (`rel=keys`), and master key (`rel=masterkey`)

Status Codes

- **200 OK** – when the token is authenticated

Changed in version 0.2.0: The response contains `"remotes_url"`, `"keys_url"`, and `"master_key_url"`, and equivalent three *Link* headers.

CLI

See also:

Configuration

geofront-server

Simple SSH key management service

```
usage: geofront-server [-h] [--create-master-key] [-d] [-v] [-H HOST]
                      [-p PORT] [--renew-master-key] [--trusted-proxy]
                      [--force-https]
                      FILE
```

file

geofront configuration file (Python script)

-h, --help

show this help message and exit

--create-master-key

create a new master key if no master key yet

```
-d, --debug
    debug mode

-v, --version
    show program's version number and exit

-H <host>, --host <host>
    host to bind [*]

-p <port>, --port <port>
    port to bind [5000]

--renew-master-key
    renew the master key before the server starts. implies --create-master-key option

--trusted-proxy
    IP address of a client allowed to override url_scheme via the X-Forwarded-Proto header. useful when it runs
    behind reverse proxy. -d/-debug option disables this option

--force-https
    enable HSTS (HTTP strict transport security) and set PREFERRED_URL_SCHEME to "https"
```

geofront-key-regen

Regen the Geofront master key

```
usage: geofront-key-regen [-h] [--create-master-key] [-d] [-v] FILE
```

```
file
    geofront configuration file (Python script)

-h, --help
    show this help message and exit

--create-master-key
    create a new master key if no master key yet

-d, --debug
    debug mode

-v, --version
    show program's version number and exit
```

Configuration

The **geofront-server** command takes a configuration file as required argument. The configuration is an ordinary Python script that defines the following required and optional variables. Note that all names have to be uppercase.

config.TEAM

(*geofront.team.Team*) The backend implementation for team authentication. For example, in order to authorize members of GitHub organization use *GitHubOrganization* implementation:

```
from geofront.backends.github import GitHubOrganization

TEAM = GitHubOrganization(
    client_id='GitHub OAuth app client id goes here',
    client_secret='GitHub OAuth app client secret goes here',
```

```
        org_login='your_org_name' # in https://github.com/your_org_name
    )
```

Or you can implement your own backend by subclassing `Team`.

See also:

Module `geofront.team` — Team authentication The interface for team authentication.

Class `geofront.backends.github.GitHubOrganization` The `Team` implementation for GitHub organizations.

Class `geofront.backends.bitbucket.BitbucketTeam` The `Team` implementation for Bitbucket Cloud teams.

Class `geofront.backends.stash.StashTeam` The `Team` implementation for Atlassian's Bitbucket Server (which was Stash).

config.REMOTE_SET

(`RemoteSet`) The set of remote servers to be managed by Geofront. It can be anything only if it's an mapping object. For example, you can hard-code it by using Python `dict` data structure:

```
from geofront.remote import Remote

REMOTE_SET = {
    'web-1': Remote('ubuntu', '192.168.0.5'),
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'worker-1': Remote('ubuntu', '192.168.0.25'),
    'worker-2': Remote('ubuntu', '192.168.0.26'),
    'db-1': Remote('ubuntu', '192.168.0.50'),
    'db-2': Remote('ubuntu', '192.168.0.51'),
}
```

Every key has to be a string, and every value has to be an instance of `Remote`. `Remote` consists of an user, a hostname, and the port to SSH. For example, if you've `ssh`-ed to a remote server by the following command:

```
$ ssh -p 2222 ubuntu@192.168.0.50
```

A `Remote` object for it should be:

```
Remote('ubuntu', '192.168.0.50', 2222)
```

You can add more dynamism by providing custom `dict`-like mapping object. `collections.abc.Mapping` could help to implement it. For example, `CloudRemoteSet` is a subtype of `Mapping`, and it dynamically loads the list of available instance nodes in the cloud e.g. EC2 of AWS. Due to Apache Libcloud it can work with more than 20 cloud providers like AWS, Azure, or Rackspace.

```
from geofront.backends.cloud import CloudRemoteSet
from libcloud.compute.types import Provider
from libcloud.compute.providers import get_driver

driver_cls = get_driver(Provider.EC2)
driver = driver_cls('access id', 'secret key', region='us-east-1')
REMOTE_SET = CloudRemoteSet(driver)
```

See also:

Class `geofront.remote.Remote` Value type that represents a remote server to `ssh`.

Class `geofront.backends.cloud.CloudRemoteSet` The Libcloud-backed dynamic remote set.

Module `collections.abc` — Abstract Base Classes for Containers This module provides abstract base classes that can be used to test whether a class provides a particular interface; for example, whether it is hashable or whether it is a mapping.

`config.TOKEN_STORE`

(`werkzeug.contrib.cache.BaseCache`) The store to save access tokens. It uses Werkzeug's cache interface, and Werkzeug provides several built-in implementations as well e.g.:

- `MemcachedCache`
- `RedisCache`
- `FileSystemCache`

For example, in order to store access tokens into Redis:

```
from werkzeug.contrib.cache import RedisCache  
  
TOKEN_STORE = RedisCache(host='localhost', db=0)
```

Of course you can implement your own backend by subclassing `BaseCache`.

Although it's a required configuration, but when `-d/-debug` is enabled, `SimpleCache` (which is all expired after `geofront-server` process terminated) is used by default.

See also:

Cache — Werkzeug Cache backend interface and implementations provided by Werkzeug.

`config.KEY_STORE`

(`geofront.keystore.KeyStore`) The store to save *public keys* for each team member. (Not the *master key*; don't be confused with `MASTER_KEY_STORE`.)

If `TEAM` is a `GitHubOrganization` object, `KEY_STORE` also can be `GitHubKeyStore`. It's an adapter class of GitHub's per-account public key list.

```
from geofront.backends.github import GitHubKeyStore  
  
KEY_STORE = GitHubKeyStore()
```

You also can store public keys into the database like SQLite, PostgreSQL, or MySQL through `DatabaseKeyStore`:

```
import sqlite3  
from geofront.backends.dbapi import DatabaseKeyStore  
  
KEY_STORE = DatabaseKeyStore(sqlite3,  
                             '/var/lib/geofront/public_keys.db')
```

Some cloud providers like Amazon EC2 and Rackspace (Next Gen) support *key pair service*. `CloudKeyStore` helps to use the service as a public key store:

```
from geofront.backends.cloud import CloudKeyStore  
from libcloud.storage.types import Provider  
from libcloud.storage.providers import get_driver
```

```
driver_cls = get_driver(Provider.EC2)
driver = driver_cls('api key', 'api secret key', region='us-east-1')
KEY_STORE = CloudKeyStore(driver)
```

New in version 0.2.0: Added `DatabaseKeyStore` class. Added `CloudKeyStore` class.

New in version 0.3.0: Added `StashKeyStore` class.

`config.MASTER_KEY_STORE`

(`geofront.masterkey.MasterKeyStore`) The store to save the *master key*. (Not *public keys*; don't be confused with `KEY_STORE`.)

The master key store should be secure, and hard to lose the key at the same time. Geofront provides some built-in implementations:

`FileSystemMasterKeyStore` It stores the master key into the file system as the name suggests. You can set the path to save the key. Although it's not that secure, but it might help you to try out Geofront.

`CloudMasterKeyStore` It stores the master key into the cloud object storage like S3 of AWS. It supports more than 20 cloud providers through the efforts of `Libcloud`.

```
from geofront.masterkey import FileSystemMasterKeyStore

MASTER_KEY_STORE = FileSystemMasterKeyStore('/var/lib/geofront/id_rsa')
```

`config.PERMISSION_POLICY`

(`PermissionPolicy`) The permission policy to determine which remotes are visible for each team member, and allowed them to SSH.

The default is `DefaultPermissionPolicy`, and it allows everyone in the team to view and access through SSH to all available remotes.

If your remote set has metadata for ACL i.e. group identifiers to allow you can utilize it through `GroupMetadataPermissionPolicy`.

If you need more subtle and complex rules for ACL you surely can implement your own policy by subclassing `PermissionPolicy` interface.

New in version 0.2.0.

`config.MASTER_KEY_TYPE`

(`Type[PKey]`) The type of the master key that will be generated. It has to be a subclass of `paramiko.pkey.PKey`:

RSA `paramiko.rsakey.RSAKey`

ECDSA `paramiko.ecdsakey.ECDSAKey`

DSA (DSS) `paramiko.dsskey.DSSKey`

`RSAKey` by default.

New in version 0.4.0.

`config.MASTER_KEY_BITS`

(`Optional[int]`) The number of bits the generated master key should be. 2048 by default.

Changed in version 0.4.0: Since the appropriate `MASTER_KEY_BITS` depends on its `MASTER_KEY_TYPE`, the default value of `MASTER_KEY_BITS` became None (from 2048).

None means to follow `MASTER_KEY_TYPE`'s own default (appropriate) bits.

New in version 0.2.0.

config.MASTER_KEY_RENEWAL

(`datetime.timedelta`) The interval of master key renewal. None means never. For example, if you want to renew the master key every week:

```
import datetime

MASTER_KEY_RENEWAL = datetime.timedelta(days=7)
```

A day by default.

config.TOKEN_EXPIRE

(`datetime.timedelta`) The time to expire each access token. As shorter it becomes more secure but more frequent to require team members to authenticate. So too short time would interrupt team members.

A week by default.

config.ENABLE_HSTS

(`bool`) Enable HSTS (HTTP strict transport security).

False by default.

New in version 0.2.2.

Example

```
# This is a configuration example. See docs/config.rst as well.

# Scenario: Your team is using GitHub, and the organization login is @YOUR_TEAM.
# All members already registered their public keys to their GitHub accounts,
# and are using git through ssh public key authorization.

# First of all, you have to decide how to authorize team members.
# Geofront provides a built-in authorization method for GitHub organizations.
# It requires a pair of client keys (id and secret) for OAuth authentication.
# You can create one from:
#
# https://github.com/organizations/YOUR_TEAM/settings/applications/new
#
# Then import GitHubOrganization class, and configure a pair of client keys
# and your organization login name (@YOUR_TEAM in here).
from geofront.backends.github import GitHubOrganization

TEAM = GitHubOrganization(
    client_id='0123456789abcdef0123',
    client_secret='0123456789abcdef0123456789abcdef01234567',
    org_login='YOUR_TEAM'
)

# Your colleagues have already registered their public keys to GitHub,
# so you don't need additional storage for public keys. We'd use GitHub
# as your public key store.
from geofront.backends.github import GitHubKeyStore

KEY_STORE = GitHubKeyStore()

# Unlike public keys, the master key ideally ought to be accessible by
# only Geofront. Assume you use Amazon Web Services. So you'll store
# the master key to the your private S3 bucket named your_team_master_key.
```

```

from geofront.backends.cloud import CloudMasterKeyStore
from libcloud.storage.types import Provider
from libcloud.storage.providers import get_driver

driver_cls = get_driver(Provider.S3)
driver = driver_cls('aws access key', 'aws secret key')
container = driver.get_container(container_name='your_team_master_key')
MASTER_KEY_STORE = CloudMasterKeyStore(driver, container, 'id_rsa')

# You have to let Geofront know what to manage remote servers.
# Although the list can be hard-coded in the configuration file,
# but you'll get the list dynamically from EC2 API. Assume our all
# AMIs are Amazon Linux, so the usernames are always ec2-user.
# If you're using Ubuntu AMIs it should be ubuntu instead.
from geofront.backends.cloud import CloudRemoteSet
from libcloud.compute.types import Provider
from libcloud.compute.providers import get_driver

driver_cls = get_driver(Provider.EC2)
driver = driver_cls('aws access id', 'aws secret key', region='west-east-1')
REMOTE_SET = CloudRemoteSet(driver, user='ec2-user')

# Suppose your team is divided by several subgroups, and these subgroups are
# represented in teams of the GitHub organization. So you can control
# who can access each remote by specifying allowed groups to its metadata.
# CloudRemoteSet which is used for above REMOTE_SET exposes each EC2 instance's
# metadata as it has. We suppose every EC2 instance has Allowed-Groups
# metadata key and its value is space-separated list of group slugs.
# The following settings will allow only members who belong to corresponding
# groups to access.
from geofront.remote import GroupMetadataPermissionPolicy

PERMISSION_POLICY = GroupMetadataPermissionPolicy('Allowed-Groups')

# Geofront provisions access tokens (or you can think them as sessions)
# for Geofront clients. Assume you already have a Redis server running
# on the same host. We'd store tokens to the db 0 on that Redis server
# in the example.
from werkzeug.contrib.cache import RedisCache

TOKEN_STORE = RedisCache(host='localhost', db=0)

```

geofront — Simple SSH key management service

geofront.backends — Backend implementations

geofront.backends.bitbucket — Bitbucket Cloud team

New in version 0.4.0.

Provides team implementation for Bitbucket Cloud (which is also known as simply Bitbucket).

In order to use Bitbucket's API you need to add an OAuth consumer. You can find the form from *Bitbucket settings* → *Access Management* → *OAuth* → *OAuth consumers* → *Add consumer*. OAuth consumer has to be set like the following:

Callback It has to be the root url of the Geofront server.

Permissions The following permissions are required:

Account Read.

It's used for identifying the authenticated Bitbucket user.

Team membership Read.

It's used for determining whether the authenticated Bitbucket user belongs to the Bitbucket team.

Other than the above are unnecessary.

Note: Not to be confused with Bitbucket Server (which was Stash). For Bitbucket Server, use `geofront.backend.stash` module instead.

Note: Unfortunately, Atlassian deprecated the existing SSH keys endpoint from their HTTP RESTful API. Unlike `geofront.backends.github` or `geofront.backends.stash`, Bitbucket Cloud cannot be used for storing/loading public keys, but can be used only for authentication and authorization. You need to use other key store implementations instead e.g. `CloudKeyStore` or `DatabaseKeyStore`.

```
class geofront.backends.bitbucket.BitbucketTeam(consumer_key: str, consumer_secret: str,
                                                team_username: str) → None
```

Authenticate team membership through Bitbucket Cloud, and authorize to access Bitbucket Cloud key store.

Note that group identifiers `list_groups()` method returns are Bitbucket team group *slugs*. You can find the list of your available group slugs in the team using Bitbucket API:

```
$ curl -u YourUsername https://api.bitbucket.org/1.0/groups/YourTeamUsername/
[
  {
    "name": "Administrators",
    "permission": "read",
    "auto_add": false,
    "slug": "administrators",
    ...
  },
  {
    "name": "Developers",
    "permission": "read",
    "auto_add": false,
    "slug": "developers",
    ...
  },
]
```

Parameters

- `consumer_key` (`str`) – bitbucket oauth consumer key
- `consumer_secret` (`str`) – bitbucket oauth consumer secret
- `team_username` (`str`) – bitbucket team account name. for example 'spoqa' in <https://bitbucket.org/spoqa>

`geofront.backends.cloud` — Libcloud-backed implementations

This module provides built-in implementations of Geofront's some core interfaces through libcloud. [Libcloud](#) is “a library for interacting with many of the popular cloud service providers using unified API.”

New in version 0.2.0.

```
class geofront.backends.cloud.CloudKeyStore(driver: libcloud.compute.base.NodeDriver,
                                             key_name_format: str = None) → None
```

Store public keys into the cloud provider’s key pair service. Note that not all providers support key pair service. For example, Amazon EC2, and Rackspace (Next Gen) support it.

```
from geofront.backends.cloud import CloudKeyStore
from libcloud.compute.types import Provider
from libcloud.compute.providers import get_driver

driver_cls = get_driver(Provider.EC2)
driver = driver_cls('api key', 'api secret key', region='us-east-1')
KEY_STORE = CloudKeyStore(driver)
```

Parameters

- **driver** (`libcloud.compute.base.NodeDriver`) – libcloud compute driver
- **key_name_format** (`str`) – the format which determines each key’s name used for the key pair service. default is `DEFAULT_KEY_NAME_FORMAT`

`DEFAULT_KEY_NAME_FORMAT = '{identity.team_type.__module__}.{identity.team_type.__qualname__} {identity.identifier} ({str})` The default key_name_format. The type name of team followed by identifier, and then key fingerprint follows e.g. `'geofront.backends.github.GitHubOrganization dahlia 00:11:22...:ff'`.

```
class geofront.backends.cloud.CloudMasterKeyStore(driver: libcloud.storage.base.StorageDriver,
                                                 container: libcloud.storage.base.Container,
                                                 object_name: str) → None
```

Store the master key into the cloud object storage e.g. AWS [S3](#). It supports more than 20 cloud providers through the efforts of [Libcloud](#).

```
from geofront.backends.cloud import CloudMasterKeyStore
from libcloud.storage.types import Provider
from libcloud.storage.providers import get_driver

driver_cls = get_driver(Provider.S3)
driver = driver_cls('api key', 'api secret key')
container = driver.get_container(container_name='my-master-key-bucket')
MASTER_KEY_STORE = CloudMasterKeyStore(container)
```

Parameters

- **driver** (`libcloud.storage.base.StorageDriver`) – the libcloud storage driver
- **container** (`libcloud.storage.base.Container`) – the block storage container
- **object_name** (`str`) – the object name to use

See also:

Object Storage — Libcloud Storage API allows you to manage cloud object storage and services such as Amazon S3, Rackspace CloudFiles, Google Storage and others.

```
class geofront.backends.cloud.CloudMasterPublicKeyStore(driver: libcloud.compute.base.NodeDriver,
key_pair_name: str,
master_key_store: geofront.masterkey.MasterKeyStore)
→ None
```

It doesn't store the whole master key, but stores only public part of the master key into cloud provider's key pair registry. So it requires the actual `master_key_store` to store the whole master key which is not only public part but also private part.

It helps to create compute instances (e.g. Amazon EC2) that are already colonized.

Parameters

- `driver` (`libcloud.compute.base.NodeDriver`) – libcloud compute driver
- `key_pair_name` (`str`) – the name for cloud provider's key pair registry
- `master_key_store` (`MasterKeyStore`) – “actual” master key store to store the whole master key

New in version 0.2.0.

```
class geofront.backends.cloud.CloudRemoteSet(driver: libcloud.compute.base.NodeDriver,
user: str = 'ec2-user', port:
int = 22, alias_namer: typing.Callable[[libcloud.compute.base.Node],
str] = <function CloudRemote-
Set.<lambda>>) → None
```

Libcloud-backed remote set. It supports more than 20 cloud providers through the efforts of Libcloud.

```
from geofront.backends.cloud import CloudRemoteSet
from libcloud.compute.types import Provider
from libcloud.compute.providers import get_driver

driver_cls = get_driver(Provider.EC2)
driver = driver_cls('access id', 'secret key', region='us-east-1')
REMOTE_SET = CloudRemoteSet(driver)
```

If the given `driver` supports metadata feature (for example, AWS EC2, Google Compute Engine, and OpenStack support it) the resulted `Remote` objects will fill their `metadata` as well.

Parameters

- `driver` (`libcloud.compute.base.NodeDriver`) – libcloud compute driver
- `user` (`str`) – the username to `ssh`. the default is 'ec2-user' which is the default user of amazon linux ami
- `port` (`int`) – the port number to `ssh`. the default is 22 which is the default `ssh` port
- `alias_namer` – A function to name an alias for the given node. `Node.name` is used by default.

See also:

Compute — Libcloud The compute component of libcloud allows you to manage cloud and virtual servers offered by different providers, more than 20 in total.

New in version 0.4.0.

Changed in version 0.2.0: It fills `metadata` of the resulted `Remote` objects if the driver supports.

`geofront.backends.dbapi` — Key store using DB-API 2.0

See also:

[PEP 249](#) — Python Database API Specification v2.0

New in version 0.2.0.

`class geofront.backends.dbapi.DatabaseKeyStore(db_module: module, *args, **kwargs) → None`

Store public keys into database through DB-API 2.0. It takes a module that implements DB-API 2.0, and arguments/keywords to its `connect()` method. For example, the following code stores public keys into SQLite 3 database:

```
import sqlite3
DatabaseKeyStore(sqlite3, 'geofront.db')
```

The following code stores public keys into PostgreSQL database through `psycopg2`:

```
import psycopg2
DatabaseKeyStore(psycopg2, database='geofront', user='postgres')
```

It will create a table named `geofront_public_key` into the database.

Parameters

- `db_module` (`types.ModuleType`) – [PEP 249](#) DB-API 2.0 compliant module
- `*args` – arguments to `db_module.connect()` function
- `**kwargs` – keyword arguments to `db_module.connect()` function

`geofront.backends.github` — GitHub organization and key store

`class geofront.backends.github.GitHubKeyStore`

Use GitHub account's public keys as key store.

`class geofront.backends.github.GitHubOrganization(client_id: str, client_secret: str, org_login: str) → None`

Authenticate team membership through GitHub, and authorize to access GitHub key store.

Note that group identifiers `list_groups()` method returns are GitHub team *slugs*. You can find what team slugs are there in the organization using GitHub API:

```
$ curl -u YourUserLogin https://api.github.com/orgs/YourOrgLogin/teams
Enter host password for user 'YourUserLogin':
[
  {
    "name": "Owners",
    "id": 111111,
    "slug": "owners",
    "permission": "admin",
    "url": "https://api.github.com/teams/111111",
    ...
  },
  {
  }
```

```
        "name": "Programmers",
        "id": 222222,
        "slug": "programmers",
        "permission": "pull",
        "url": "https://api.github.com/teams/222222",
        ...
    }
]
```

In the above example, `owners` and `programmers` are team slugs.

Parameters

- `client_id (str)` – github api client id
- `client_secret (str)` – github api client secret
- `org_login (str)` – github org account name. for example '`spoqa`' in <https://github.com/spoqa>

`geofront.backends.oauth` — Team backend bases for OAuth

New in version 0.4.0.

`class geofront.backends.oauth.OAuth2Team(client_id: str, client_secret: str) → None`

Base implementation of `Team` for OAuth 2. Every subclass has to implement the following attributes and methods:

- `authorize_url` attribute
- `access_token_url` attribute
- `scope` attribute
- `determine_identity()` method
- `authorize()` method

`access_token_url = NotImplemented`

(`str`) The url to issue an OAuth 2 access token.

Note: Concrete subclass has to implement this method.

`authorize_scope = NotImplemented`

(`str`) The scope string for OAuth 2 authorization.

Note: Concrete subclass has to implement this method.

`authorize_url = NotImplemented`

(`str`) The OAuth 2 authorization url.

Note: Concrete subclass has to implement this method.

`determine_identity(access_token: str) → geofront.identity.Identity`

Determine `Identity` from the given access token.

Note: Concrete subclass has to implement this method.

unauthorized_identity_message_format = ‘identity {identity} is unauthorized’

(*str*) The message template which is used when the authenticated identity is unauthorized. There’s a predefined default message, but it can be overridden by subclass. The two keywords are available:

identity (*Identity*) The authenticated identity.

team (*OAuth2Team*) The actual team object.

`geofront.backends.oauth.request(access_token, url: str, method: str = 'GET', data: bytes = None)`

Make a request to GitHub API, and then return the parsed JSON result.

Parameters

- **access_token** (*str*, *Identity*) – api access token string, or *Identity* instance
- **url** (*str*) – the api url to request
- **method** (*str*) – an optional http method. ‘GET’ by default
- **data** (*bytes*) – an optional content body

`geofront.backends.stash` — Bitbucket Server team and key store

New in version 0.3.0.

Provides implementations of team and key store for Atlassian’s Bitbucket Server (which was Stash).

Note: Not to be confused with Bitbucket Cloud. As from September 22, Atlassian Stash becomes Bitbucket Server. For Bitbucket Cloud, use `geofront.backends.bitbucket` module instead.

`class geofront.backends.stash.StashKeyStore(team: geofront.backends.stash.StashTeam) → None`

Use Bitbucket Server (Stash) account’s public keys as key store.

`class geofront.backends.stash.StashTeam(server_url: str, consumer_key: str, rsa_key: str) → None`

Authenticate team membership through Bitbucket Server (which was Stash), and authorize to access Bitbucket Server key store.

Parameters

- **server_url** (*str*) – the base url of the bitbucket server (stash server)
- **consumer_key** (*str*) – the consumer key (client id)

`geofront.identity` — Member identification

`class geofront.identity.Identity(team_type: typing.Type[typing.Team], identifier: collections.abc.Hashable, access_token=None) → None`

Hashable value object which purposes to identify the owner of each public key in the store.

Parameters

- **team_type** (*Type[Team]*) – a subclass of *Team*

- **identifier** (`Hashable`) – any hashable identifier for the owner. It's interpreted by `team_type`
- **access_token** – an optional access token which may be used by key store

access_token = None

An optional access token which may be used by key store.

Note: The attribute is ignored by `==`, `=` operators, and `hash()` function.

identifier = None

(`Hashable`) Any hashable identifier for the owner. It's interpreted by `team_type`.

team_type = None

(`Type[Team]`) A subclass of `Team`.

geofront.keystore — Public key store

`geofront.keystore.KEY_TYPES = {'ssh-rsa': <class 'paramiko.rsakey.RSAKey'>, 'ssh-dss': <class 'paramiko.dsskey.DSSKey'>, 'ecdsa-sha2-nistp256': <class 'paramiko.ecdsa_key.ECDSAKey'>, 'ecdsa-sha2-nistp384': <class 'paramiko.ecdsa_key.ECDSAKey'>, 'ecdsa-sha2-nistp512': <class 'paramiko.ecdsa_key.ECDSAKey'>}`
(`Mapping[str, Type[Pkey]]`) The mapping of supported key types.

New in version 0.4.0: Added `ecdsa-sha2-nistp256`, `ecdsa-sha2-nistp384`, and `ecdsa-sha2-nistp512` (`ECDSAKey`) support.

exception geofront.keystore.AuthorizationError

Authorization exception that rise when the given identity has no required permission to the key store.

exception geofront.keystore.DuplicatePublicKeyError

Exception that rise when the given public key is already registered.

class geofront.keystore.KeyStore

The key store backend interface. Every key store has to guarantee that public keys are unique for all identities i.e. the same public key can't be registered across more than an identity.

deregister (`identity: geofront.identity.Identity, public_key: paramiko.pkey.PKey`) → `None`

Remove the given `public_key` of the `identity`. It silently does nothing if there isn't the given `public_key` in the store.

Parameters

- **identity** – the owner identity
- **public_key** (`paramiko.pkey.PKey`) – the public key to remove

Raises `geofront.keystore.AuthorizationError` – when the given `identity` has no required permission to the key store

list_keys (`identity: geofront.identity.Identity`) → `typing.AbstractSet[paramiko.pkey.PKey]`

List registered public keys of the given `identity`.

Parameters `identity` (`Identity`) – the owner of keys to list

Returns the set of `paramiko.pkey.PKey` owned by the `identity`

Return type `AbstractSet`

Raises `geofront.keystore.AuthorizationError` – when the given `identity` has no required permission to the key store

register (`identity: geofront.identity.Identity, public_key: paramiko.pkey.PKey`) → `None`

Register the given `public_key` to the `identity`.

Parameters

- **identity** – the owner identity
- **public_key** (`paramiko.PKey`) – the public key to register

Raises

- `geofront.keystore.AuthorizationError` – when the given identity has no required permission to the key store
- `geofront.keystore.DuplicatePublicKeyError` – when the public_key is already in use

exception `geofront.keystore.KeyStoreError`Exceptions related to `KeyStore` are an instance of this.**exception** `geofront.keystore.KeyTypeError`

Unsupported public key type raise this type of error.

`geofront.keystore.format_openssh_pubkey(key: paramiko.PKey) → str`Format the given key to an OpenSSH public key line, used by `authorized_keys`, `id_rsa.pub`, etc.**Parameters** `key` (`paramiko.PKey`) – the key object to format**Returns** a formatted openssh public key line**Return type** `str``geofront.keystore.get_key_fingerprint(key: paramiko.PKey, glue: str = ':') → str`

Get the hexadecimal fingerprint string of the key.

Parameters

- **key** (`paramiko.PKey`) – the key to get fingerprint
- **glue** (`str`) – glue character to be placed between bytes. ':' by default

Returns the fingerprint string**Return type** `str``geofront.keystore.parse_openssh_pubkey(line: str) → paramiko.PKey`Parse an OpenSSH public key line, used by `authorized_keys`, `id_rsa.pub`, etc.**Parameters** `line` (`str`) – a line of public key**Returns** the parsed public key**Return type** `paramiko.PKey`**Raises**

- `ValueError` – when the given line is an invalid format
- `KeyTypeError` – when it's an unsupported key type

Changed in version 0.4.0: Added `ecdsa-sha2-nistp256`, `ecdsa-sha2-nistp384`, and `ecdsa-sha2-nistp521` (`ECDSAKey`) support.**`geofront.masterkey` — Master key management**

Master key renewal process:

1. Create a new master key without updating the master key store.
2. Update every `authorized_keys` to authorize both the previous and the new master keys.

3. Store the new master key to the master key store, and remove the previous master key.
4. Update very `authorized_keys` to authorize only the new master key.

For more details, see also [TwoPhaseRenewal](#).

Changed in version 0.2.0: `CloudMasterKeyStore` is moved from this module to `geofront.backends.cloud`. See [CloudMasterKeyStore](#).

exception `geofront.masterkey.EmptyStoreError`

Exception that rises when there's no master key yet in the store.

class `geofront.masterkey.FileSystemMasterKeyStore(path: str) → None`

Store the master key into the file system. Although not that secure, but it might help you to evaluate Geofront.

Parameters `path` (`str`) – the path to save file. it has to end with the filename

Raises `OSSError` – when the `path` is not writable

exception `geofront.masterkey.KeyGenerationError`

A subtype of `ValueError` which rise when failed to generate a key.

New in version 0.4.0.

class `geofront.masterkey.MasterKeyStore`

The master key store backend interface. It can have only one master key at the most.

load() → `paramiko.pkey.PKey`

Load the stored master key.

Returns the stored master key

Return type `paramiko.pkey.PKey`

Raises `geofront.masterkey.EmptyStoreError` – when there's no master key yet in the store

save(master_key: paramiko.pkey.PKey) → `None`

Remove the stored master key, and then save the new master key. The operation should be atomic.

Parameters `master_key` (`paramiko.pkey.PKey`) – the new master key to replace the existing master key

class `geofront.masterkey.PeriodicalRenewal(servers: typing.AbstractSet[geofront.remote.Remote], key_store: geofront.masterkey.MasterKeyStore, interval: datetime.timedelta, key_type: typing.Type[paramiko.pkey.PKey] = <class 'paramiko.rsakey.RSAKey'>, bits: typing.Union[int, NoneType] = None, start: bool = True) → None`

Periodically renew the master key in the separated background thread.

Parameters

- `servers` (`AbstractSet[Remote]`) – servers to renew the master key. every element has to be an instance of `Remote`
- `key_store` (`MasterKeyStore`) – the master key store to update
- `interval` (`datetime.timedelta`) – the interval to renew
- `key_type` (`Type[PKey]`) – the type of a new master key. it has to be a subclass of `PKey`. `RSAKey` by default. (the default `key_type` can change in the future.)

- **bits** (Optional[int]) – the number of bits the generated key should be. if `key_type` is `RSAKey` it has to be 512 at least. the default value is `None`, which means to `key_type`'s own default (appropriate) bits
- **start** (bool) – whether to start the background thread immediately. `True` by default

New in version 0.4.0: The `key_type` optional parameter.

Changed in version 0.4.0: Since the appropriate `bits` depends on its `key_type`, the default value of `bits` became `None` (from 2048). `None` means to follow `key_type`'s own default (appropriate) bits.

New in version 0.2.0: The `bits` optional parameter.

`terminate()`

Graceful termination.

```
class geofront.masterkey.TwoPhaseRenewal(servers: typing.AbstractSet[geofront.remote.Remote],
                                         old_key: paramiko.pkey.PKey, new_key:
                                         paramiko.pkey.PKey) → None
```

Renew the master key for the given `servers`. It's a context manager for `with` statement.

```
# State: servers allow only old_key;
#         old_key is in the master_key_store
with TwoPhaseRenewal(servers, old_key, new_key):
    # State: *servers allow both old_key and new_key; *
    #         old_key is in the master_key_store
    master_key_store.save(new_key)
    # State: servers allow both old_key and new_key;
    #         *new_key is in the master_key_store.*

# State: *servers allow only new_key; *
#         new_key is in the master_key_store
```

Parameters

- **servers** (`AbstractSet[Remote]`) – the set of `Remote` servers to renew their master key
- **old_key** (`paramiko.pkey.PKey`) – the previous master key to expire
- **new_key** (`paramiko.pkey.PKey`) – the new master key to replace `old_key`

```
geofront.masterkey.generate_key(key_type: typing.Type[paramiko.pkey.PKey] = <class
                                         'paramiko.rsakey.RSAKey'>, bits: typing.Union[int, NoneType] = None) → paramiko.pkey.PKey
```

Generate a new key of the given `key_type`. If `bits` is omitted generate one with an appropriate bits.

Parameters

- **key_type** (`Type[PKey]`) – the type of a new master key. it has to be a subclass of `PKey`. `RSAKey` by default. (the default `key_type` can change in the future.)
- **bits** – the number of bits the generated key should be. if `key_type` is `RSAKey` it has to be 512 at least. the default value is `None`, which means to `key_type`'s own default (appropriate) bits

Returns a generate key which is an instance of the given `key_type`

Return type `PKey`

Raises `KeyGenerationError` – when it failed to generate a key using given options (`key_type` and `bits`)

New in version 0.4.0.

```
geofront.masterkey.read_private_key_file(file_: typing.IO[str]) → paramiko.pkey.PKey
```

Read a private key file. Similar to `PKey.from_private_key()` except it guess the key type.

Parameters `file` (`IO[str]`) – a stream of the private key to read

Returns the read private key

Return type `paramiko.pkey.PKey`

Raises `paramiko.ssh_exception.SSHException` – when something goes wrong

```
geofront.masterkey.renew_master_key(servers: typing.AbstractSet[geofront.remote.Remote],  
                                     key_store: geofront.masterkey.MasterKeyStore,  
                                     key_type: typing.Type[paramiko.pkey.PKey] = <class  
                                         'paramiko.rsa.RSAKey'>,  
                                     bits: typing.Union[int,  
                                         NoneType] = None) → paramiko.pkey.PKey
```

Renew the master key. It creates a new master key, makes servers to authorize the new key, replaces the existing master key with the new key in the `key_store`, and then makes servers to deauthorize the old key. All these operations are done in a two-phase renewal transaction.

Parameters

- `servers` (`AbstractSet[Remote]`) – servers to renew the master key. every element has to be an instance of `Remote`
- `key_store` (`MasterKeyStore`) – the master key store to update
- `key_type` (`Type[PKey]`) – the type of a new master key. it has to be a subclass of `PKey`. `RSAKey` by default. (the default `key_type` can change in the future.)
- `bits` (`Optional[int]`) – the number of bits the generated key should be. if `key_type` is `RSAKey` it has to be 512 at least. the default value is `None`, which means to `key_type`'s own default (appropriate) bits

Returns the created new master key

Return type `paramiko.pkey.PKey`

New in version 0.4.0: The `key_type` optional parameter.

Changed in version 0.4.0: Since the appropriate `bits` depends on its `key_type`, the default value of `bits` became `None` (from 2048). `None` means to follow `key_type`'s own default (appropriate) bits.

New in version 0.2.0: The `bits` optional parameter.

geofront.regen — Regen master key

New in version 0.2.0.

```
geofront.regen.main()
```

The main function of `geofront-key-regen` CLI program.

```
geofront.regen.main_parser(parser: argparse.ArgumentParser = None) → argparse.ArgumentParser
```

Create an `ArgumentParser` object for `geofront-key-regen` CLI program. It also is used for documentation through `sphinxcontrib-autoprogram`.

Returns a properly configured `ArgumentParser`

Return type `argparse.ArgumentParser`

```
geofront.regen.regenerate(master_key_store: geofront.masterkey.MasterKeyStore, remote_set:
    typing.Mapping[str, geofront.remote.Remote], key_type: typing.Type[paramiko.pkey.PKey] = <class 'paramiko.rsakey.RSAKey'>, bits: typing.Union[int, NoneType] = None, *, create_if_empty: bool, renew_unless_empty: bool) → None
```

Regenerate or create the master key.

geofront.remote — Remote sets

Every `RemoteSet` is represented as a mapping (which is immutable, or mutable) of alias `str` to `Remote` object e.g.:

```
{
    'web-1': Remote('ubuntu', '192.168.0.5'),
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'worker-1': Remote('ubuntu', '192.168.0.25'),
    'worker-2': Remote('ubuntu', '192.168.0.26'),
    'db-1': Remote('ubuntu', '192.168.0.50'),
    'db-2': Remote('ubuntu', '192.168.0.51'),
}
```

However, in the age of the cloud, you don't have to manage the remote set since the most of cloud providers offer their API to list provisioned remote nodes.

Geofront provides builtin `CloudRemoteSet`, a subtype of `RemoteSet` (which is alias of `Mapping[str, Remote]`), that proxies to the list dynamically made by cloud providers.

Changed in version 0.2.0: `CloudRemoteSet` is moved from this module to `geofront.backends.cloud`. See `CloudRemoteSet`.

```
class geofront.remote.AuthorizedKeyList(sftp_client: paramiko.sftp_client.SFTPClient) → None
    List-like abstraction for remote authorized_keys.
```

Note that the contents are all lazily evaluated, so in order to pretend heavy duplicate communications over SFTP use `list()` to eagerly evaluate e.g.:

```
lazy_list = AuthorizedKeyList(sftp_client)
eager_list = list(lazy_list)
# ... some modifications on eager_list ...
lazy_list[:] = eager_list
```

Parameters `sftp_client` (`paramiko.sftp_client.SFTPClient`) – the remote sftp connection to access `authorized_keys`

`FILE_PATH = '.ssh/authorized_keys'`
`(str)` The path of `authorized_keys` file.

```
class geofront.remote.DefaultPermissionPolicy
    All remotes are listed and allowed for everyone in the team.
```

New in version 0.2.0.

```
class geofront.remote.GroupMetadataPermissionPolicy(metadata_key: str, separator: str =
    None) → None
    Allow/disallow remotes according their metadata. It assumes every remote has a metadata key that stores a set of groups to allow. For example, suppose there's the following remote set:
```

```
{
    'web-1': Remote('ubuntu', '192.168.0.5', metadata={'role': 'web'}),
    'web-2': Remote('ubuntu', '192.168.0.6', metadata={'role': 'web'}),
    'web-3': Remote('ubuntu', '192.168.0.7', metadata={'role': 'web'}),
    'worker-1': Remote('ubuntu', '192.168.0.25',
                        metadata={'role': 'worker'}),
    'worker-2': Remote('ubuntu', '192.168.0.26',
                        metadata={'role': 'worker'}),
    'db-1': Remote('ubuntu', '192.168.0.50', metadata={'role': 'db'}),
    'db-2': Remote('ubuntu', '192.168.0.51', metadata={'role': 'db'})
}
```

and there are groups identified as 'web', 'worker', and 'db'. So the following policy would allow only members who belong to the corresponding groups:

`GroupMetadataPermissionPolicy('role')`

Parameters

- **metadata_key** (`str`) – the key to find corresponding groups in metadata of each remote
- **separator** (`str`) – the character separates multiple group identifiers in the metadata value. for example, if the groups are stored as like '`sysadmin,owners`' then it should be `,`. it splits group identifiers by all whitespace characters by default

New in version 0.2.0.

`class geofront.remote.PermissionPolicy`

Permission policy determines which remotes are visible by a team member, and which remotes are allowed to SSH. So each remote can have one of three states for each team member:

Listed and allowed A member can SSH to the remote.

Listed but disallowed A member can be aware of the remote, but cannot SSH to it.

Unlisted and disallowed A member can't be aware of the remote, and can't SSH to it either.

Unlisted but allowed It is possible in theory, but mostly meaningless in practice.

The implementation of this interface has to implement two methods. One is `filter()` which determines whether remotes are listed or unlisted. Other one is `permit()` which determines whether remotes are allowed or disallowed to SSH.

New in version 0.2.0.

filter (`remotes: typing.Mapping[str, geofront.remote.Remote], identity: geofront.identity.Identity, groups: typing.AbstractSet[collections.abc.Hashable]`) → `typing.Mapping[str, geofront.remote.Remote]`

Determine which ones in the given `remotes` are visible to the `identity` (which belongs to `groups`). The resulted mapping of filtered remotes has to be a subset of the input `remotes`.

Parameters

- **remotes** (`RemoteSet`) – the remotes set to filter. keys are alias strings and values are `Remote` objects
- **identity** (`Identity`) – the identity that the filtered remotes would be visible to
- **groups** (`GroupSet`) – the groups that the given `identity` belongs to. every element is a group identifier and `Hashable`

Returns the filtered result remote set

Return type `RemoteSet`

permit (`remote: geofront.remote.Remote, identity: geofront.identity.Identity, groups: typing.AbstractSet[collections.abc.Hashable]`) → `bool`

Determine whether to allow the given `identity` (which belongs to `groups`) to SSH the given `remote`.

Parameters

- **remote** (`Remote`) – the remote to determine
- **identity** (`Identity`) – the identity to determine
- **groups** (`GroupSet`) – the groups that the given `identity` belongs to. every element is a group identifier and `Hashable`

class `geofront.remote.Remote` (`user: str, host: str, port: int = 22, metadata: typing.Mapping[str, object] = {}`) → `None`

Remote node to SSH.

Parameters

- **user** (`str`) – the username to `ssh`
- **host** (`str`) – the host to access
- **port** (`int`) – the port number to `ssh`. the default is 22 which is the default `ssh` port
- **metadata** (`Mapping[str, object]`) – optional metadata mapping. keys and values have to be all strings. empty by default

New in version 0.2.0: Added optional `metadata` parameter.

host = None

(`str`) The hostname to access.

metadata = None

(`Mapping[str, object]`) The additional metadata. Note that it won't affect to `hash()` of the object, nor ==/= comparison of the object.

New in version 0.2.0.

port = None

(`int`) The port number to SSH.

user = None

(`str`) The username to SSH.

geofront.remote.RemoteSet

The abstract type for remote sets. Keys are strings and values are `Remote` objects.

Alias of `AbstractSet[str, Remote]`.

New in version 0.4.0.

alias of `Mapping`

class `geofront.remote.RemoteSetFilter` (`filter: typing.Callable[[str, geofront.remote.Remote], bool], remote_set: typing.Mapping[str, geofront.remote.Remote]`) → `None`

It takes a `filter` function and a `remote_set`, and then return a filtered set of remotes.

```
>>> remotes = {
...     'web-1': Remote('ubuntu', '192.168.0.5'),
...     'web-2': Remote('ubuntu', '192.168.0.6'),
...     'web-3': Remote('ubuntu', '192.168.0.7'),
...     'worker-1': Remote('ubuntu', '192.168.0.25'),
```

```
...     'worker-2': Remote('ubuntu', '192.168.0.26'),
...     'db-1': Remote('ubuntu', '192.168.0.50'),
...     'db-2': Remote('ubuntu', '192.168.0.51'),
...
>>> filtered = RemoteSetFilter(
...     lambda a, r: a == 'web' or r.host.endswith('5'),
...     remotes
... )
>>> dict(filtered)
{
    'web-1': Remote('ubuntu', '192.168.0.5'),
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'worker-1': Remote('ubuntu', '192.168.0.25')
}
```

The key difference of this and conditional dict comprehension is evaluation time. (TL;DR: the contents of `RemoteSetFilter` is evaluated everytime its filtered result is needed.)

If `remote_set` is an ordinary `dict` object, `RemoteSetFilter` is not needed. But if `remote_set` is, for example, `CloudRemoteSet`, the filtered result of dict comprehension on it is fixed at Geofront's configuration loading time. That means `geofront-cli remotes` doesn't change even if the list of remotes in the cloud is changed.

On the other hand, the filtered result of `RemoteSetFilter` is never fixed, because the filter on `remote_set` is always evaluated again when its `__iter__()`/`__getitem__()`/etc are called.

```
>>> remotes['web-4'] = Remote('ubuntu', '192.168.0.8')
>>> del remotes['worker-1']
>>> dict(filtered)
{
    'web-1': Remote('ubuntu', '192.168.0.5'),
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'web-4': Remote('ubuntu', '192.168.0.25'), # this replaced worker-1!
}
```

Parameters

- `filter` (`Callable[[str, Remote], bool]`) – a filter function which takes key (alias name) and `Remote`, and `False` if exclude it, or `True` if include it
- `remote_set` (`RemoteSet`) – a set of remotes. it has to be a mapping of alias name to `Remote`

New in version 0.3.1.

`class geofront.remote.RemoteSetUnion(*remote_sets) → None`

It takes two or more remote sets, and then return a union set of them. Note that the order of arguments affect overriding of aliases (keys). If there are any duplicated aliases (keys), the latter alias (key) is prior to the former.

```
>>> a = {
...     'web-1': Remote('ubuntu', '192.168.0.5'),
...     'web-2': Remote('ubuntu', '192.168.0.6'),
...     'web-3': Remote('ubuntu', '192.168.0.7'),
...     'worker-1': Remote('ubuntu', '192.168.0.8'),
...
>>> b = {
```

```

...
    'worker-1': Remote('ubuntu', '192.168.0.25'),
...
    'worker-2': Remote('ubuntu', '192.168.0.26'),
...
    'db-1': Remote('ubuntu', '192.168.0.27'),
...
    'db-2': Remote('ubuntu', '192.168.0.28'),
...
    'db-3': Remote('ubuntu', '192.168.0.29'),
...
}
>>> c = {
...
    'web-1': Remote('ubuntu', '192.168.0.49'),
...
    'db-1': Remote('ubuntu', '192.168.0.50'),
...
    'db-2': Remote('ubuntu', '192.168.0.51'),
...
}
>>> union = RemoteSetUnion(a, b, c)
>>> dict(union)
{
    'web-1': Remote('ubuntu', '192.168.0.49'),
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'worker-1': Remote('ubuntu', '192.168.0.25'),
    'worker-2': Remote('ubuntu', '192.168.0.26'),
    'db-1': Remote('ubuntu', '192.168.0.50'),
    'db-2': Remote('ubuntu', '192.168.0.51'),
    'db-3': Remote('ubuntu', '192.168.0.29'),
}

```

Note that `RemoteSetUnion` is evaluated everytime its contents is needed, like `RemoteSetFilter`:

```

>>> del c['web-1']
>>> dict(union)
{
    'web-1': Remote('ubuntu', '192.168.0.5'), # changed!
    'web-2': Remote('ubuntu', '192.168.0.6'),
    'web-3': Remote('ubuntu', '192.168.0.7'),
    'worker-1': Remote('ubuntu', '192.168.0.25'),
    'worker-2': Remote('ubuntu', '192.168.0.26'),
    'db-1': Remote('ubuntu', '192.168.0.50'),
    'db-2': Remote('ubuntu', '192.168.0.51'),
    'db-3': Remote('ubuntu', '192.168.0.29'),
}

```

Parameters `*remote_sets` (`RemoteSet`) – two or more remote sets. every remote set has to be a mapping of alias `str` to `Remote`

New in version 0.3.2.

`geofront.remote.authorize(public_keys: typing.AbstractSet[paramiko.pkey.PKey], master_key: paramiko.pkey.PKey, remote: geofront.remote.Remote, timeout: datetime.timedelta) → datetime.datetime`

Make an one-time authorization to the remote, and then revokes it when `timeout` reaches soon.

Parameters

- `public_keys` (`AbstractSet[paramiko.pkey.PKey]`) – the set of public keys to authorize
- `master_key` (`paramiko.pkey.PKey`) – the master key (*not owner's key*)
- `remote` (`Remote`) – a remote to grant access permission
- `timeout` (`datetime.timedelta`) – the time an authorization keeps alive

Returns the expiration time

Return type `datetime.datetime`

geofront.server — Key management service

Although Geofront provides `geofront-server`, a CLI to run the server, it also provides an interface as a WSGI application as well. Note that there might be some limitations like lack of periodical master key renewal.

First of all, the server needs a configuration, there are several ways to configure it.

`app.config.from_pyfile()` If you can freely execute arbitrary Python code before starting the server, this method is the most straightforward way to configure the server. Note that the argument should be an absolute path, because it interprets paths relative to the path of Geofront program, not the current working directory (CWD).

There are also other methods as well:

- `from_object()`
- `from_json()`
- `from_envvar()`

`GEOFONT_CONFIG` If you can't execute any arbitrary Python code, set the `GEOFONT_CONFIG` environment variable. It's useful when to use a CLI frontend of the WSGI server e.g. `gunicorn`, `waitress-serve`.

```
$ GEOFONT_CONFIG="/etc/geofront.cfg.py" gunicorn geofront.server:app
```

Then you can run a Geofront server using your favorite WSGI server. Pass the following WSGI application object to the server. It's a documented endpoint for WSGI:

```
geofront.server:app
geofront.server.AUTHORIZATION_TIMEOUT = datetime.timedelta(0, 60)
(datetime.timedelta) How long does each temporary authorization keep alive after it's issued. A minute.

class geofront.server.FingerprintConverter(*args, **kwargs)
    Werkzeug custom converter which accepts valid public key fingerprints.

class geofront.server.Token(identity, expires_at)
    The named tuple type that stores a token.

    expires_at
        Alias for field number 1

    identity
        Alias for field number 0

class geofront.server.TokenIdConverter(*args, **kwargs)
    Werkzeug custom converter which accepts valid token ids.

geofront.server.add_public_key(token_id: str)
    Register a public key to the token. It takes an OpenSSH public key line through the request content body.
```

```
POST /tokens/0123456789abcdef/keys/ HTTP/1.1
Accept: application/json
Content-Type: text/plain

ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjbCx.../MuLLzC/m8Q==
```

```
HTTP/1.1 201 Created
Content-Type: text/plain
Location: /tokens/0123456789abcdef/keys/
→50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47

ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjBcX.../MuLLzC/m8Q==
```

Parameters `token_id(str)` – the token id that holds the identity

Status 201 when key registration is successful

Status 400 (unsupported-key-type) when the key type is unsupported, or (invalid-key) the key format is invalid, or (duplicate-key) the key is already used

Status 415 (unsupported-content-type) when the *Content-Type* is not *text/plain*

`geofront.server.app = <Flask ‘geofront.server’>`
`(flask.Flask)` The WSGI application of the server.

`geofront.server.authenticate(token_id: str)`
Finalize the authentication process. It will be shown on web browser.

Parameters `token_id(str)` – token id created by *create_access_token()*

Status 400 when authentication is failed

Status 404 when the given `token_id` doesn't exist

Status 403 when the `token_id` is already finalized

Status 200 when authentication is successfully done

`geofront.server.authorize_remote(token_id: str, alias: str)`

Temporarily authorize the token owner to access a remote. A made authorization keeps alive in a minute, and then will be expired.

```
POST /tokens/0123456789abcdef/remotes/web-1/ HTTP/1.1
Accept: application/json
Content-Length: 0
```

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "success": "authorized",
  "remote": {"user": "ubuntu", "host": "192.168.0.5", "port": 22},
  "expires_at": "2014-04-14T14:57:49.822844+00:00"
}
```

Parameters

- `token_id(str)` – the token id that holds the identity
- `alias(str)` – the alias of the remote to access

Status 200 when successfully granted a temporary authorization

Status 404 (not-found) when there's no such remote

geofront.server.**create_access_token**(token_id: str)

Create a new access token.

```
PUT /tokens/0123456789abcdef/ HTTP/1.1
Accept: application/json
Content-Length: 0
```

```
HTTP/1.1 202 Accepted
Content-Type: application/json
Date: Tue, 15 Apr 2014 03:44:43 GMT
Expires: Tue, 15 Apr 2014 04:14:43 GMT
Link: <https://example.com/login/page/?redirect_uri=...>; rel=next

{
    "next_url": "https://example.com/login/page/?redirect_uri=..."
}
```

Parameters `token_id` (str) – an arbitrary token id to create. it should be enough random to avoid duplication

Status 202 when the access token is prepared

Resheader Link the link owner's browser should redirect to

geofront.server.**delete_public_key**(token_id: str, fingerprint: bytes)

Delete a public key.

```
DELETE /tokens/0123456789abcdef/keys/
↪50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47/ HTTP/1.1
Accept: application/json
```

```
HTTP/1.1 200 OK
Content-Type: application/json

{
    "72:00:60:24:66:e8:2d:4d:2a:2a:a2:0e:7b:7f:fc:af":
        "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCom2CDLekY...5CeYsvSdrTWA5",
    "78:8a:09:c8:c1:24:5c:89:76:92:b0:1e:93:95:5d:48":
        "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEA16iSKKjFHOGj...kD62SYXNKY9c=",
    "ab:3a:fb:30:44:e3:5e:1e:10:a0:c9:9a:86:f4:67:59":
        "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAQEAzzF8c07pzgKk...r+b6Q9VnWWQ=="
}
```

Parameters

- `token_id` (str) – the token id that holds the identity
- `fingerprint` (bytes) – the fingerprint of a public key to delete

Status 200 when the public key is successfully deleted

Status 404 (not-found) when there's no such public key

geofront.server.**get_identity**(token_id: str) → geofront.identity.Identity

Get the identity object from the given `token_id`.

Parameters `token_id` (str) – the token id to get the identity it holds

Returns the identity the token holds

Return type *Identity*

Raises `werkzeug.exceptions.HTTPException` – 404 Not Found (token-not-found) when the token does not exist. 412 Precondition Failed (unfinished-authentication) when the authentication process is not finished yet. 410 Gone (expired-token) when the token was expired. 403 Forbidden (not-authorized) when the token is not unauthorized.

`geofront.server.get_key_store() → geofront.keystore.KeyStore`

Get the configured key store implementation.

Returns the configured key store

Return type *KeyStore*

Raises `RuntimeError` – when 'KEY_STORE' is not configured, or it's not an instance of `KeyStore`

`geofront.server.get_master_key_store() → geofront.masterkey.MasterKeyStore`

Get the configured master key store implementation.

Returns the configured master key store

Return type *MasterKeyStore*

Raises `RuntimeError` – when 'MASTER_KEY_STORE' is not configured, or it's not an instance of `MasterKeyStore`

`geofront.server.get_permission_policy() → geofront.remote.PermissionPolicy`

Get the configured permission policy.

Returns the configured permission policy

Return type *PermissionPolicy*

Raises `RuntimeError` – if 'PERMISSION_POLICY' is not configured, or it's not an instance of `PermissionPolicy`

New in version 0.2.0.

`geofront.server.get_public_key(token_id: str, fingerprint: bytes) → paramiko.pkey.PKey`

Internal function to find the public key by its fingerprint.

Parameters

- `token_id` (`str`) – the token id that holds the identity
- `fingerprint` (`bytes`) – the fingerprint of a public key to find

Returns the found public key

Return type `paramiko.pkey.PKey`

Raises `werkzeug.exceptions.HTTPException` – (not-found) when there's no such public key

`geofront.server.get_remote_set() → typing.Mapping[str, geofront.remote.Remote]`

Get the configured remote set.

Returns the configured remote set

Return type `RemoteSet`

Raises `RuntimeError` – if 'REMOTE_SET' is not configured, or it's not a mapping object

`geofront.server.get_team() → geofront.team.Team`

Get the configured team implementation, an instance of `team.Team`.

It raises `RuntimeError` if 'TEAM' is not configured.

`geofront.server.get_token_store()` → `werkzeug.contrib.cache.BaseCache`
Get the configured token store, an instance of `werkzeug.contrib.cache.BaseCache`.

It raises `RuntimeError` if 'TOKEN_STORE' is not configured, but it just warns `RuntimeWarning` when it comes to debug mode.

Returns the configured session store

Return type `werkzeug.contrib.cache.BaseCache`

Raises `RuntimeError` – when 'TOKEN_STORE' is not configured, or the value is not an instance of `werkzeug.contrib.cache.BaseCache`

`geofront.server.list_public_keys(token_id: str)`

List registered keys to the token owner.

```
GET /tokens/0123456789abcdef/keys/ HTTP/1.1
Accept: application/json
```

HTTP/1.1 200 OK

`Content-Type: application/json`

```
{
    "50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47": 
        "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQgQDAEMUvjbC.../MuLLzC/m8Q== ",
    "72:00:60:24:66:e8:2d:4d:2a:2a:a2:0e:7b:7f:fc:af": 
        "ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQCom2CDLekY...5CeYsvSdrTWA5 ",
    "78:8a:09:c8:c1:24:5c:89:76:92:b0:1e:93:95:5d:48": 
        "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEA16iSKKjFHOgj...kD62SYXNKY9c= ",
    "ab:3a:fb:30:44:e3:5e:1e:10:a0:c9:9a:86:f4:67:59": 
        "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAQEAzzF8c07pzgKk...r+b6Q9VnWWQ== "
}
```

Parameters `token_id` (`str`) – the token id that holds the identity

Status 200 when listing is successful, even if there are no keys

`geofront.server.main()`

The main function for `geofront-server` CLI program.

`geofront.server.main_parser()` → `argparse.ArgumentParser`

Create an `ArgumentParser` object for `geofront-server` CLI program. It also is used for documentation through `sphinxcontrib-autoprogram`.

Returns a properly configured `ArgumentParser`

Return type `argparse.ArgumentParser`

`geofront.server.master_key()`

Public part of the master key in OpenSSH authorized_keys (public key) format.

```
GET /masterkey/ HTTP/1.1
Accept: text/plain
```

HTTP/1.1 200 OK

`Content-Type: text/plain`

```
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAQgQDAEMUvjbC.../MuLLzC/m8Q==
```

Status 200 when the master key is available

Status 500 when the master key is unavailable

`geofront.server.public_key(token_id: str, fingerprint: bytes)`

Find the public key by its fingerprint if it's registered.

```
GET /tokens/0123456789abcdef/keys/50:5a:9a:12:75:8b:b0:88:7d:7a:8d:66:29:63:d0:47/
  ↳ HTTP/1.1
Accept: text/plain
```

```
HTTP/1.1 200 OK
Content-Type: text/plain
```

```
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjBcX.../MuLLzC/m8Q==
```

Parameters

- `token_id` (`str`) – the token id that holds the identity
- `fingerprint` (`bytes`) – the fingerprint of a public key to find

Status 200 when the public key is registered

Status 404 (not-found) when there's no such public key

`geofront.server.remote_dict(remote: geofront.remote.Remote) → typing.Mapping[str, typing.Union[str, int]]`

Convert a `remote` to a simple dictionary that can be serialized to JSON.

Parameters `remote` (`Remote`) – a remote instance to serialize

Returns the converted dictionary

Return type `Mapping[Union[str, int]]`

`geofront.server.server_endpoint()`

The endpoint of HTTP API which provide the url to create a new token.

```
GET /
Accept: application/json
```

```
HTTP/1.0 200 OK
Content-Type: application/json
Link: <https://example.com/tokens/>; rel=tokens
Link: <https://example.com/masterkey/>; rel=masterkey

{
  "master_key_url": "https://example.com/masterkey/",
  "tokens_url": "https://example.com/tokens/"
}
```

Resheader Link the url to create a new token. the equivalent to the response content

Status 200 when the server is available

New in version 0.4.0: Added "master_key_url" field in the result and `Link` header of `rel=masterkey`.

New in version 0.2.0.

`geofront.server.server_version(response: flask.wrappers.Response) → flask.wrappers.Response`

Indicate the version of Geofront server using `Server` and `X-Geofront-Version` headers.

`geofront.server.token(token_id: str)`

The owner identity that the given token holds if the token is authenticated. Otherwise it responds 403 Forbidden, 404 Not Found, 410 Gone, or 412 Precondition Failed. See also `get_identity()`.

```
GET /tokens/0123456789abcdef/ HTTP/1.1
```

```
Accept: application/json
```

```
HTTP/1.0 200 OK
```

```
Content-Type: application/json
```

```
Link: <https://example.com/tokens/0123456789abcdef/remotes/>; rel=remotes
```

```
Link: <https://example.com/tokens/0123456789abcdef/keys/>; rel=keys
```

```
Link: <https://example.com/masterkey/>; rel=masterkey
```

```
{
    "identifier": "dahlia",
    "team_type": "geofront.backends.github.GitHubOrganization",
    "remotes_url": "https://example.com/tokens/0123456789abcdef/remotes/",
    "keys_url": "https://example.com/tokens/0123456789abcdef/keys/",
    "master_key_url": "https://example.com/masterkey/"
}
```

Parameters `token_id(str)` – the token id that holds the identity

Resheader Link the url to list remotes (`rel=remotes`), public keys (`rel=keys`), and master key (`rel=masterkey`)

Status 200 when the token is authenticated

Changed in version 0.2.0: The response contains `"remotes_url"`, `"keys_url"`, and `"master_key_url"`, and equivalent three `Link` headers.

`geofront.server.token_master_key(token_id: str)`

Public part of the master key in OpenSSH authorized_keys (public key) format.

```
GET /tokens/0123456789abcdef/masterkey/ HTTP/1.1
```

```
Accept: text/plain
```

```
HTTP/1.1 301 Moved Permanently
```

```
Content-Type: text/plain
```

```
ssh-rsa AAAAB3NzaC1yc2EAAAQABAAAAgQDAEMUvjBcX.../MuLLzC/m8Q==
```

Parameters `token_id(str)` – the token id that holds the identity

Status 200 when the master key is available

Status 500 when the master key is unavailable

Deprecated since version 4.0.0: Use `GET /masterkey/` instead.

Changed in version 4.0.0: It now responds with 301 Moved Permanently instead of 200 OK. It redirects to `GET /masterkey/` which is the new master key url.

`geofront.server.url_for(endpoint, **kwargs)`

The almost same to `flask.url_for()` except it's sensitive to `PREFERRED_URL_SCHEME` configuration.

geofront.team — Team authentication

Geofront doesn't force you to manage team members by yourself. Instead it hides how to manage team members, and offers `Team`, the layering interface to implement custom team data provider e.g. `GitHubOrganization`.

It is theoretically possible to implement a straightforward RDBMS-backed team provider, but we rather recommend to adapt your existing team data instead e.g. `GitHub organization`, `Google Apps organization`, `Bitbucket team`.

class `geofront.team.AuthenticationContinuation(next_url: str, state) → None`

The continuation value for the process between `Team.request_authentication()` and `Team.authenticate()`.

It is created by `Team.request_authentication()` method, and holds following two attributes:

next_url

(`str`) The url to direct the authenticator to.

state

The arbitrary value to be passed to `Team.authenticate()` method's `state` parameter.

It can be used for passing arbitrary nonce, or request token, etc.

It has to be possible to pickle.

New in version 0.3.0.

exception `geofront.team.AuthenticationError`

Authentication exception which rise when the authentication process has trouble including network problems.

`geofront.team.GroupSet`

The type to represent a set of groups. Group sets consist of group identifiers. Group identifiers are usually a string, but can be anything hashable.

Alias of `AbstractSet[Hashable]`.

New in version 0.4.0.

alias of `AbstractSet`

class `geofront.team.Team`

Backend interface for team membership authentication.

Authorization process consists of three steps (and therefore every backend subclass has to implement these three methods):

1. `request_authentication()` makes the url to interact with the owner of the identity to authenticate.

I.e. the url to login web page of the backend service.

2. `authenticate()` finalize authentication of the identity, and then returns `Identity`.

3. `authorize()` tests the given `Identity` belongs to the team. It might be a redundant step for several backends, but is a necessary step for some backends that distinguish identity authentication between team membership authorization. For example, Any Gmail users can authenticate they own their Gmail account, but only particular users can authenticate their account belongs to the configured Google Apps organization.

`authenticate(state, requested_redirect_url: str, wsgi_environ: typing.Mapping[str; object]) → geofront.identity.Identity`

Second step of authentication process, to create a verification token for the identity. The token is used by `authorize()` method, and the key store as well (if available).

Parameters

- `state` – `AuthenticationContinuation.state` vaule returned by `request_authentication()` method

- `requested_redirect_url` (`str`) – a url that was passed to `request_authentication()`'s `redirect_url` parameter
- `wsgi_environ` (`Mapping[str, object]`) – forwarded wsgi environ dictionary

Returns an identity which contains a verification token

Return type `Identity`

Raises `geofront.team.AuthenticationError` – when something goes wrong e.g. network errors, the user failed to verify their ownership

Changed in version 0.3.0: The `auth_nonce` parameter was replaced by more general `state` parameter. The new parameter has no longer type constraints so that it can be any value even if it's not a `str`.

`authorize(identity: geofront.identity.Identity) → bool`

The last step of authentication process. Test whether the given `identity` belongs to the team.

Note that it can be called every time the owner communicates with Geofront server, out of authentication process.

Parameters `identity` (`Identity`) – the identity to authorize

Returns True only if the `identity` is a member of the team

Return type `bool`

`list_groups(identity: geofront.identity.Identity) → typing.AbstractSet[collections.abc.Hashable]`

List the all groups that the given `identity` belongs to. Any hashable value can be an element to represent a group e.g.:

```
{1, 4, 9}
```

Or:

```
{'owners', 'programmers'}
```

Whatever value the set consists of these would be referred by `Remote` objects.

Some team implementations might not have a concept like groups. It's okay to return always an empty set then.

Parameters `identity` (`Identity`) – the identity to list his/her groups

Returns the set of groups associated with the `identity`

Return type `GroupSet`

New in version 0.2.0.

`request_authentication(redirect_url: str) → geofront.team.AuthenticationContinuation`

First step of authentication process, to prepare the “sign in” interaction with the owner. It typically returns a url to the login web page.

Parameters `redirect_url` (`str`) – a url that owner's browser has to redirect to after the “sign in” interaction finishes

Returns a url to the web page to interact with the owner in their browser

Return type `AuthenticationContinuation`

Changed in version 0.3.0: The `auth_nonce` parameter was removed. Instead, it became to return `AuthenticationContinuation` value so that share state more general than simple `auth_nonce` between `request_authentication()` and `authenticate()`. If arbitrary nonce is needed, `request_authentication()` method has to generate one by itself.

geofront.version — Version data

`geofront.version.VERSION = '0.4.0'`

(`str`) The version string e.g. '1.2.3'.

`geofront.version.VERSION_INFO = (0, 4, 0)`

(`Tuple[int, int, int]`) The triple of version numbers e.g. (1, 2, 3).

CHAPTER 8

Indices and tables

- genindex
- modindex
- search

HTTP Routing Table

/

GET /, 22

/masterkey

GET /masterkey/, 22

/tokens

GET /tokens/ (token_id:token_id) /, 26

GET /tokens/ (token_id:token_id) /authenticate/,
24

GET /tokens/ (token_id:token_id) /keys/,
25

GET /tokens/ (token_id:token_id) /keys/ (fingerprint:fingerprint) /,
23

GET /tokens/ (token_id:token_id) /masterkey/,
24

GET /tokens/ (token_id:token_id) /remotes/,
24

POST /tokens/ (token_id:token_id) /keys/,
25

POST /tokens/ (token_id:token_id) /remotes/ (alias) /,
22

PUT /tokens/ (token_id:token_id) /, 26

DELETE /tokens/ (token_id:token_id) /keys/ (fingerprint:fingerprint) /,
23

Python Module Index

C

config, 28

g

geofront, 33
geofront.backends, 33
geofront.backends.bitbucket, 33
geofront.backends.cloud, 34
geofront.backends.dbapi, 37
geofront.backends.github, 37
geofront.backends.oauth, 38
geofront.backends.stash, 39
geofront.identity, 39
geofront.keystore, 40
geofront.masterkey, 41
geofront.regen, 44
geofront.remote, 45
geofront.server, 50
geofront.team, 56
geofront.version, 58

Symbols

-create-master-key
 geofront-key-regen command line option, 28
 geofront-server command line option, 27
-force-https
 geofront-server command line option, 28
-renew-master-key
 geofront-server command line option, 28
-trusted-proxy
 geofront-server command line option, 28
-H <host>, --host <host>
 geofront-server command line option, 28
-d, --debug
 geofront-key-regen command line option, 28
 geofront-server command line option, 27
-h, --help
 geofront-key-regen command line option, 28
 geofront-server command line option, 27
-p <port>, --port <port>
 geofront-server command line option, 28
-v, --version
 geofront-key-regen command line option, 28
 geofront-server command line option, 28

A

access_token (geofront.identity.Identity attribute), 40
access_token_url (geofront.backends.oauth OAuth2Team attribute), 38
add_public_key() (in module geofront.server), 50
app (in module geofront.server), 51
authenticate() (geofront.team.Team method), 57
authenticate() (in module geofront.server), 51
AuthenticationContinuation (class in geofront.team), 57
AuthenticationError, 57
AUTHORIZATION_TIMEOUT (in module geofront.server), 50
AuthorizationError, 40
authorize() (geofront.team.Team method), 58
authorize() (in module geofront.remote), 49

authorize_remote() (in module geofront.server), 51
authorize_scope (geofront.backends.oauth OAuth2Team attribute), 38
authorize_url (geofront.backends.oauth OAuth2Team attribute), 38

AuthorizedKeyList (class in geofront.remote), 45

B

BitbucketTeam (class in geofront.backends.bitbucket), 34

C

CloudKeyStore (class in geofront.backends.cloud), 35
CloudMasterKeyStore (class in geofront.backends.cloud), 35
CloudMasterPublicKeyStore (class in geofront.backends.cloud), 36
CloudRemoteSet (class in geofront.backends.cloud), 36
config (module), 28
create_access_token() (in module geofront.server), 51

D

DatabaseKeyStore (class in geofront.backends.dbapi), 37
DEFAULT_KEY_NAME_FORMAT (geofront.backends.cloud.CloudKeyStore attribute), 35

DefaultPermissionPolicy (class in geofront.remote), 45
delete_public_key() (in module geofront.server), 52
deregister() (geofront.keystore.KeyStore method), 40
determine_identity() (geofront.backends.oauth OAuth2Team method), 38

DuplicatePublicKeyError, 40

E

EmptyStoreError, 42
ENABLE_HSTS (in module config), 32
environment variable
 GEOFONT_CONFIG, 50
expires_at (geofront.server.Token attribute), 50

F

file

 geofront-key-regen command line option, 28
 geofront-server command line option, 27

FILE_PATH (geofront.remote.AuthorizedKeyList attribute), 45

FileSystemMasterKeyStore (class in geofront.masterkey), 42

filter() (geofront.remote.PermissionPolicy method), 46

FingerprintConverter (class in geofront.server), 50

format_openssh_pubkey() (in module geofront.keystore), 41

G

generate_key() (in module geofront.masterkey), 43

geofront (module), 33

geofront-key-regen command line option

 --create-master-key, 28

 -d, --debug, 28

 -h, --help, 28

 -v, --version, 28

 file, 28

geofront-server command line option

 --create-master-key, 27

 --force-https, 28

 --renew-master-key, 28

 --trusted-proxy, 28

 -H <host>, --host <host>, 28

 -d, --debug, 27

 -h, --help, 27

 -p <port>, --port <port>, 28

 -v, --version, 28

 file, 27

geofront.backends (module), 33

geofront.backends.bitbucket (module), 33

geofront.backends.cloud (module), 34

geofront.backends.dbapi (module), 37

geofront.backends.github (module), 37

geofront.backends.oauth (module), 38

geofront.backends.stash (module), 39

geofront.identity (module), 39

geofront.keystore (module), 40

geofront.masterkey (module), 41

geofront.regen (module), 44

geofront.remote (module), 45

geofront.server (module), 50

geofront.team (module), 56

geofront.version (module), 58

GEOFRONT_CONFIG, 50

get_identity() (in module geofront.server), 52

get_key_fingerprint() (in module geofront.keystore), 41

get_key_store() (in module geofront.server), 53

get_master_key_store() (in module geofront.server), 53

get_permission_policy() (in module geofront.server), 53

get_public_key() (in module geofront.server), 53

get_remote_set() (in module geofront.server), 53

get_team() (in module geofront.server), 53

get_token_store() (in module geofront.server), 54

GitHubKeyStore (class in geofront.backends.github), 37

GitHubOrganization (class in geofront.backends.github), 37

GroupMetadataPermissionPolicy (class in geofront.remote), 45

GroupSet (in module geofront.team), 57

H

host (geofront.remote.Remote attribute), 47

I

identifier (geofront.identity.Identity attribute), 40

Identity (class in geofront.identity), 39

identity (geofront.server.Token attribute), 50

K

KEY_STORE (in module config), 30

KEY_TYPES (in module geofront.keystore), 40

KeyGenerationError, 42

KeyStore (class in geofront.keystore), 40

KeyStoreError, 41

KeyTypeError, 41

L

list_groups() (geofront.team.Team method), 58

list_keys() (geofront.keystore.KeyStore method), 40

list_public_keys() (in module geofront.server), 54

load() (geofront.masterkey.MasterKeyStore method), 42

M

main() (in module geofront.regen), 44

main() (in module geofront.server), 54

main_parser() (in module geofront.regen), 44

main_parser() (in module geofront.server), 54

master_key() (in module geofront.server), 54

MASTER_KEY_BITS (in module config), 31

MASTER_KEY_RENEWAL (in module config), 31

MASTER_KEY_STORE (in module config), 31

MASTER_KEY_TYPE (in module config), 31

MasterKeyStore (class in geofront.masterkey), 42

metadata (geofront.remote.Remote attribute), 47

N

next_url (geofront.team.AuthenticationContinuation attribute), 57

O

OAuth2Team (class in geofront.backends.oauth), 38

P

parse_openssh_pubkey() (in module geofront.keystore),
[41](#)
 PeriodicalRenewal (class in geofront.masterkey), [42](#)
 PERMISSION_POLICY (in module config), [31](#)
 PermissionPolicy (class in geofront.remote), [46](#)
 permit() (geofront.remote.PermissionPolicy method), [47](#)
 port (geofront.remote.Remote attribute), [47](#)
 public_key() (in module geofront.server), [55](#)
 Python Enhancement Proposals
 PEP 249, [37](#)

[39](#)

url_for() (in module geofront.server), [56](#)
 user (geofront.remote.Remote attribute), [47](#)

V

VERSION (in module geofront.version), [59](#)
 VERSION_INFO (in module geofront.version), [59](#)

R

read_private_key_file() (in module geofront.masterkey),
[43](#)
 regenerate() (in module geofront.regen), [44](#)
 register() (geofront.keystore.KeyStore method), [40](#)
 Remote (class in geofront.remote), [47](#)
 remote_dict() (in module geofront.server), [55](#)
 REMOTE_SET (in module config), [29](#)
 RemoteSet (in module geofront.remote), [47](#)
 RemoteSetFilter (class in geofront.remote), [47](#)
 RemoteSetUnion (class in geofront.remote), [48](#)
 renew_master_key() (in module geofront.masterkey), [44](#)
 request() (in module geofront.backends.oauth), [39](#)
 request_authentication() (geofront.team.Team method),
[58](#)

S

save() (geofront.masterkey.MasterKeyStore method), [42](#)
 server_endpoint() (in module geofront.server), [55](#)
 server_version() (in module geofront.server), [55](#)
 StashKeyStore (class in geofront.backends.stash), [39](#)
 StashTeam (class in geofront.backends.stash), [39](#)
 state (geofront.team.AuthenticationContinuation attribute), [57](#)

T

Team (class in geofront.team), [57](#)
 TEAM (in module config), [28](#)
 team_type (geofront.identity.Identity attribute), [40](#)
 terminate() (geofront.masterkey.PeriodicalRenewal method), [43](#)
 Token (class in geofront.server), [50](#)
 token() (in module geofront.server), [56](#)
 TOKEN_EXPIRE (in module config), [32](#)
 token_master_key() (in module geofront.server), [56](#)
 TOKEN_STORE (in module config), [30](#)
 TokenIdConverter (class in geofront.server), [50](#)
 TwoPhaseRenewal (class in geofront.masterkey), [43](#)

U

unauthorized_identity_message_format (geofront.backends.oauth OAuth2Team attribute),